

NANO-CERAMIC®

WWW.NANO-CERAMIC.COM INDUSTRIAL PROTECTIVE COATINGS



Public Transport

What is NANO-CERAMIC Thin Film Coating?

NANO-CERAMIC Thin Film Coating is a revolutionary, ultra-durable, thin film ceramic clear-coating that provides superior scratchresistance and semi-permanent protection for all exterior and interior yacht surfaces.



Jetpack
VideoPress

What makes NANO-CERAMIC Thin Film Coating so different?

NANO-CERAMIC Thin Film Coating is more than 4 times stronger than factory paint finishes and can absorb damage that would otherwise affect the appearance and integrity of your paint. This extremely durable ceramic coating reduces swirl marks and light scratches while protecting and preserving factory paint.



Conventional paints like acrylic urethane are simply not strong enough.


NANO-CERAMIC Thin Film Coating is completely resistant to acidic environmental substances like bird droppings, bug residue, acid rain, and tree sap, unlike your vehicle's factory paint, which can be permanently etched and damaged by these substances.

NANO-CERAMIC Thin Film Coating provides advanced protective barriers to your train body and hull surfaces, maintaining both high-gloss and matte finishes.


What are the benefits of applying NANO-CERAMIC Thin Film Coating?

NANO-CERAMIC Thin Film Coating provides trains with a superior, near-permanent, clear coating that is resistant to chemical etching, harder than factory paint finishes, and able to greatly reduce swirl marks and fine scratches while leaving a superior, hydrophobic surface that is easier to clean and stays cleaner longer.


Clearcoat, Glass hull and body materials can be treated with one of our CERAMIC Thin Film Coating Restore the color and shine with advanced hydrophobic and UV protection. Even chrome, aluminum, and other metals can have added protection, as our coatings can withstand temperatures of over 850°C




Step 1 The surface layer of factory gelcoat is damaged and contaminated.



Step 2 Decontamination and polishing the gelcoat to produce a smooth and even surface.



Step 3 Restoration of coating thickness with a super-durable layer of NANO-CERAMIC





APPLY
MOVIE SCAN
QR CODE



APPLY
MOVIE SCAN
QR CODE

SIO3 WET LOOK

Body & Windshield Protection for clearcoat & glass



Product ID : SIO31A00-1L 8 Micron SIO21A00-1L 2 Micron
Consumption : +/- 2ml/m²
Reachable area : +/- 500m² Body + 500m² Windshield
Used for : Clearcoat, acrylic, glass, chrome, stainless
Application field : Public Transport

Your Fleet will stand out! These Kit-Sets contain all to make trucks and busses protected with a High-Tech ceramic layer.

- Two simple steps: Clean with our Steril Cleaner and Apply
- The original surface is protected against corrosion.
- Makes the surface anti scratch, much easier and quicker to clean, and the adhesion of dirt is reduced drastically.
- Promotes more hygienic surfaces.
- Graffiti will be easy to remove


This coating has an outstanding hydrophobic effect, and the surface stays cleaner longer. Cleaning intervals as well as the formation of water spots will be greatly reduced.

Lasts for 5 Years+ (2 Years on Glass)

How to use: Page 18

- Easy to apply**
- Cut cleaning costs**
- Anti-water spot
Anti-corrosion**
- Super hydrophobic**
- Self-cleaning stays cleaner longer**
- Anti-scratch**
- Anti-fingerprint**
- Visibility safety**
- Protects your investment**

Applicator:



SIO5 MATTE

Body & Windshield Protection for clearcoat & glass



Product ID : SIO51A00-1L 8 Micron SIO21A00-1L 2 Micron
Consumption : +/- 2ml/m²
Reachable area : +/- 500m² Body + 500m² Windshield
Used for : Clearcoat, acrylic, glass, chrome, stainless
Application field : Public Transport

Your Fleet will stand out! These Kit-Sets contain all to make trucks and busses protected with a High-Tech ceramic layer.

- Two simple steps: Clean with our Steril Cleaner and Apply
- The original surface is protected against corrosion.
- Makes the surface anti scratch, much easier and quicker to clean, and the adhesion of dirt is reduced drastically.
- Promotes more hygienic surfaces.
- Graffiti will be easy to remove

This coating has an outstanding hydrophobic effect, and the surface stays cleaner longer. Cleaning intervals as well as the formation of water spots will be greatly reduced.

Lasts for 5 Years+ (2 Years on Glass)

How to use: Page 18

- Easy to apply**
- Cut cleaning costs**
- Anti-water spot
Anti-corrosion**
- Super hydrophobic**
- Self-cleaning stays cleaner longer**
- Anti-scratch**
- Anti-fingerprint**
- Visibility safety**
- Protects your investment**

Applicator:





APPLY
MOVIE SCAN
QR CODE

STEP

One Step Polish for scratch removal

Product ID : STEP0250 250ml
Consumption : 5ml/m²
Used for : Clearcoat, gelcoat, glass and acrylic
Application field : Public Transport




Only this High Quality Polish Compound together with the recommended pads assure that every yacht can be polished from deep scratches till high gloss/zero swirl in one single step.

This saves an enormous amount on working hours as polishing takes normally 65% of the total process to make a yacht a thin film nano layer.

Purple Wool Heavy Cutting Pad cuts like natural sheepskin but finishes like a polish pad. Aggressively removes P1500 grit scratches, leaving a lustrous finish with no hazing by reducing compounding swirls.

The Cutting Pad is constructed with a blue foam and white microfiber. The Micro Cutting Pad with orange foam and white microfiber, the Polishing Pad is constructed with a black foam and black microfiber.

The pad serie is available 5.5 inch and 3 inch.

-  **Cut polish costs**
-  **Zero swirl and hologram**

Applicator:



APPLY
MOVIE SCAN
QR CODE

CLEAN

Steril Cleaner for hard surfaces

Product ID : CLEAN0500 500ml / CLEAN5000 5L
CLEAN020L 20L
Consumption : +/- 3.3ml/m²
Used for : Clearcoat, gelcoat, glass, chrome, mirrors
Application field : Public Transport



100% Steril with nano interlock technology (active lifting encapsulate the grease from the surface)

- Surface cleaning and residue removal.
- Cleaning gloves, notebooks, phones or any other item entering the cleanroom.
- Wipe down for pass-through to controlled environments.
- Pretreatment for the application of thin film coating

-  **Easy to apply spray & wipe**
-  **Indoor Outdoor**
-  **Remove grease**
-  **100% Steril**
-  **No streaking**

100% Steril

Applicator:





APPLY
MOVIE SCAN
OR CODE



SCRUB

Scrub Cleaner for hard surfaces

Product ID : SCRUB0250 500 ml / SCRUB5000 5L
SCRUB020L 20L

Consumption : +/- 2.5 ml/m²

Used for : Hard surfaces

Application field : Public Transport

Scrub Pretreatment Cleaner is a smooth rubbing compound, suitable for scrubbing glass, steel, porcelain and many other materials without scratching the surface.

If you need more scouring power, then please use our specially designed scrub pad.

Leaves no scratches behind after treatment



Non-scratching

Applicators:



APPLY
MOVIE SCAN
OR CODE



SIRP

Repellent Protector for glass / ceramics / mirrors

Product ID : SIRP0500 500ml SIRP5000 5L
SIRP020L 20L

Consumption : +/- 2 ml/m²

Used for : Glass, acrylic, aluminium chrome, vinyl

Application field : Public Transport

SIRP is an ultra long-lasting invisible surface coating which forms semi-permanent molecular bonds with the surface. The main function of treating hard surfaces with SIRP is to seal tiny pores, making it a smoother surface that will repel water and contaminants. This product is indispensable for bathrooms

- Two simple steps: Clean with our Steril Cleaner and Apply
- Makes the surface much easier and quicker to clean, and the adhesion of dirt is reduced drastically.
- Promotes more hygienic surfaces
- This coating has an outstanding hydrophobic effect, and the surface stays cleaner longer. Cleaning intervals as well as the formation of water spots will be greatly reduced.

Will last 12 washes



How to use: Page 18



Easy to apply



Indoor
Outdoor



Cut cleaning costs



Anti-water spot



Super
hydrophobic



Self-cleaning
Stays cleaner longer



Visibility
Safety

Applicator:





APPLY
MOVIE SCAN
OR CODE



MPCL

Multi Purpose Cleaner for all interior surfaces

Product ID	: MPCL0500 500 ml / MPCL5000 5L MPCL020L 20L
Consumption	: +/- 2.5ml/m ²
Used for	: Cleaning all interior surfaces
Application field	: Public Transport

The All-Purpose Cleaner is a fast, all-surface interior cleaner, low foaming, odor free, and especially suitable for removing stubborn stains from carpets, fabrics, vinyl, plastics and leather safely.

- It is very easy to clean dirt.
- Ready-to-use mixture with the right chemical strength and safe to use
- Of course it is safe for the surface of fabrics, carpets, plastics, leather, rubber and does not fade paint.
- Quickly remove dirt, dust and food scraps

Safe to use does not harm the surface



-  **Easy to apply
spray & wipe**
-  **No discoloration**
-  **Indoor
Outdoor**
-  **Quick to use**
-  **Spills are easy
to remove**
-  **Cleaner for longer**

Aplikator:



APPLY
MOVIE SCAN
OR CODE



SHRE

Pure Shine Shampoo for all exterior surfaces

Product ID	: SHRE1000 1L / SHRE5000 5L SHRE020L 20L (Drum on request)
Consumption	: 20ml : 10 Liter Water
Application field	: Public Transport

Reactivating Pure Shine Shampoo is an advanced technology, multi-purpose foaming cleaner containing a rinsing aid that will leave hard surfaces nearly dry after rinsing with clean water.

To assure the "easy-to-clean" effect that our nano layers provide, surfaces should be free of dyes, waxes or polymer sealants.





This multi-purpose cleaner contains no polymers or colors and will not leave a film of chemicals behind on the surface.

100% Safe to use for cleaning all non-porous surfaces and meets food grade classification for kitchens.

Contains no colouring chemicals which can discolor surfaces.

Dilution ratio 1: 500 (super economical)




-  **Easy to apply**
-  **Easy to clean**
-  **Stays cleaner
longer**
-  **Food grade**

Applicator:




Thin Film Protection Plan for Trains



Thin Film Maintenance Plan for Trains



Where to use Thin Film coatings:



HOW TO USE:

NANO-CERAMIC SIRP-SIO3-SIO5 MAX Thin film coatings

These products can be stored for up to 24 months (*in a dry, temperature-stable, dark environment*)

Ambient temperature:

5-30° C Avoid direct sunlight and/or high air humidity.

CLEANING

Clean the surface thoroughly with our Steril Cleaner until it is absolutely clean. If necessary, use our Scrub Cleaner or Reactivating Pure Shine Shampoo in advance. Make sure that all contamination is removed so that the glass coating can bind properly onto a clean surface. Make sure that the surface is completely dry before application!

APPLICATION OF SIRP

Spray a layer of nano SIRP on the surface and rub it in with a dry microtowel, keep rubbing it into the surface with strong pressure and wipe until all the product is even and scrubbed and only a little hazing / residue is visible **gently** wipe off this hazing / residue with a clean microfiber cloth after about a minute There is only a little pressure needed to remove the hazing completely. Curing time 1 hour.

APPLICATION OF SIO3-SIO5

Our coatings have best results on new on almost like new surfaces, we recommend to polish the surface if needed. Wear nitril gloves to clean the surface with our Steril Pretreatment Cleaner. (without wearing gloves, the oil from your hands may appear via the towel onto the surface) !!

Use more than one clean cloth to remove the dirt from the surface. (Please make sure you don't brush the dirt around on the surface by using dirty clothes.) Making the clearcoat-chrome-glass-surface clean is the most important issue. If the surface is not super steril than you will experience chemical reactions between our coatings and the still available contamination what is then visible into the ceramic layer when it is cured. In that case you will need to polish the surface again. So please don't hurry in carrying out this preparation work, but instead focus on this for 100%.

Learn the right application technique > Watch and Study the Apply Video scanning the QR Code on this page or on the packaging

(fragment BASE COAT SIBC) OPTIONAL

Use nitril gloves! Remove the plastic inner closure from the bottle and put in the dripper. Shake bottle before use! We recommend to apply the surface in easy to handle segments of about 15"x 15"inch, following the panels shape and corner lines and use these lines for overlaps. Put 8-10 drops BASE COAT on the suede mini towel using the applicator block underneath, divide the coating properly by going 3 times over the same surface, wait till it lights up (+/- 25sec) and remove the residue carefully, and buff it lightly use a separate micro towel for this. Wait 2 hours before you continue with the application of one of our hydrophobic Top Coatings. After 2 hours BASE COAT is 80% cured and ready to receive one of our TOP COATINGS. After about 7 days the BASE COATING has been fully cured and is almost unremovable.

(fragment TOP COAT **SIO3-SIO5**)

Use nitril gloves! Remove the plastic inner closure from the bottle and put in the dripper.

Shake t

he bottle before use! We recommend to apply the surface in easy to handle segments following the panel shape and corner lines and use these lines for overlaps. Put 6-8 drops 15"x 15"inch, (if start use more drops as the towel is otherwise too dry) TOP COATING on the suede mini towel using the applicator block underneath.

Start dividing it from out of the middle of the surface and keep spreading it around by light pressure in criss-cross motions. until the product is evenly distributed. MOST IMPORTANT keep on doing this till no product residue is visible anymore. If you use too much coating and/or spreading it out from example one start position in a corner of a panel then you will not be able to divide it properly towards the other side and it will roll-up on each other and form a not equal layer.


To use too much coating and not divide it equally is the second most critical point !! When you apply TOP COATING in this correct way, then there is no need to use a micro towel for polishing anymore.

(fragment **WINDSHIELD SIO2**)

Apply the nano layer WINDSHIELD COATING with the cotton apply pad. Spread 10-15 drops 20"x 25"inch of WINDSHIELD COATING on the cotton pad and apply rubb it in motions on the windshield with firm pressure until all of the product is evenly distributed and only very little residue is visible.

Remove the coating residue with a soft clean microfiber cloth after about a minute and buff the glass/panels gently to take the veils away. There is not much pressure necessary to remove it completely. Note: dry the dripper and close the bottles tightly if you want to save the content for future use. At normal ambient temperature the Nano layers are sufficiently cured after approximately 6 hours (or 2 hours Infrared) (avoid water contact during this time).

Application Video SGS (Test Reports)



SGS

What is NANO-CERAMIC Permanent Coating?

NANO-CERAMIC permanent coating is the latest generation of protective coating which transforms paint into a hard ceramic, providing superior scratch resistance and permanent protection for all exterior or interior surfaces.


NANO-CERAMIC permanent coating is 300°C resistant and more than 4 times stronger than traditional acrylic based paint finishes, and is effectively preventing damage that would otherwise affect the appearance and integrity of the original surface.

Zero Maintenance for 3 decades to come!

Our NANO-CERAMIC permanent coating is rigorously tested by an independent testing laboratory according to the European standard for outdoor paints (EN 1504-2) please find the test report on our website.

Can NANO-CERAMIC Permanent Coating be applied on any surface?


The NANO-CERAMIC permanent coating can be applied directly or indirectly on all kinds of interior and /or exterior surfaces (absorbing and non-absorbing), such as concrete, steel, wood, acrylic, gypsum and many more.



Is NANO-CERAMIC Permanent Coating self-cleaning?

NANO-CERAMIC permanent coating provides a permanent hydrophobic surface that is self cleaning, easier to clean and stays cleaner longer as water and dirt can not penetrate the ceramic layer. NANO-CERAMIC permanent coating is resistant to water vapor and water absorption.

Cross Section of Coating System



Conventional paints

Conventional gelcoats are a mixture with Epoxy or polyester resins, of which the quality of resin and pigments are the most important factor in the ultimate strength.

Most have a lifespan of 15 years, with hardness and color retention (sun fading) being the most common problems in keeping the desired object at an aesthetically pleasing level.

There is no better option than protecting your trains with a NANO-CERAMIC Thin Film or Permanent Coating!

Do not wait till the surface get worse, most easy is to apply wipe or spray when the surfaces are still in new or in nearly new condition and the cost do not outweigh the benefits



SI11

2-Component (2K)

Topcoat Transparent for Glossy surfaces

Product ID	: SI112000 2L / 1.900 gr
Consumption	: 3 layers +/- 270gr/m ² - 285ml/m ² 75 micron = 7m ²
Reachable area	: 2 layers +/- 180gr/m ² - 190ml/m ² 50 micron = 14m ²
	: 1 layers +/- 90gr/m ² - 95ml/m ² 25 micron = 21m ²
Hardness	: H9
Used for	: Concrete, steel, wood, acrylic, gypsum
Application field	: Concrete, steel, aluminium, plastics, wood, gypsum

SI11 is an incredibly strong 2-component paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating is permanent hydrophobic.
- Restores damaged finishes and reduces cleaning intervals.
- Resistant to all kinds of chemicals and UV radiation.
- Superior anti-pollution and anti-corrosion properties.
- This coating can withstand temperatures of 300°C.

Expected life duration up to 30 years+



How to use: Page 24



SI12

2-Component (2K)

Topcoat Transparent for matte surfaces

Product ID	: SI122000 2L / 2.000 gr
Consumption	: 3 layers +/- 270gr/m ² - 285ml/m ² 75 micron = 7m ²
Reachable area	: 2 layers +/- 180gr/m ² - 190ml/m ² 50 micron = 14m ²
	: 1 layers +/- 90gr/m ² - 95ml/m ² 25 micron = 21m ²
Hardness	: H9
Used for	: Concrete, steel, wood, acrylic, gypsum
Application field	: Concrete, steel, aluminium, plastics, wood, gypsum

SI12 is an incredibly strong 2-component paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating is permanent hydrophobic.
- Restores damaged finishes and reduces cleaning intervals.
- Resistant to all kinds of chemicals and UV radiation.
- Superior anti-pollution and anti-corrosion properties.
- This coating can withstand temperatures of 300°C.

Expected life duration up to 30 years+



How to use: Page 24





SI11

2-Component (2K)

Topcoat Transparent for Glossy surfaces

Product ID	: SI112000 2L / 1.900 gr
Consumption	: 3 layers +/- 270gr/m ² - 285ml/m ² 75 micron = 7m ²
Reachable area	: 2 layers +/- 180gr/m ² - 190ml/m ² 50 micron = 14m ²
	: 1 layers +/- 90gr/m ² - 95ml/m ² 25 micron = 21m ²
Hardness	: H9
Used for	: Concrete, steel, wood, acrylic, gypsum
Application field	: Concrete, steel, aluminium, plastics, wood, gypsum

SI11 is an incredibly strong 2-component paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating is permanent hydrophobic.
- Restores damaged finishes and reduces cleaning intervals.
- Resistant to all kinds of chemicals and UV radiation.
- Superior anti-pollution and anti-corrosion properties
- Graffiti will be easy to remove.
- This coating can withstand temperatures of 300°C.

Expected life duration up to 30 years+



How to use: Page 24



SI21

2-Component (2K)

The Strongest Medium White topcoat colorable

Product ID	: SI212000 2L / 2.400 gr
Consumption	: 3 layers +/- 200gr/m ² - 165ml/m ² 90 micron = 7m ²
Reachable area	: 2 layers +/- 130gr/m ² - 110ml/m ² 60 micron = 14m ²
	: 1 layers +/- 65gr/m ² - 55ml/m ² 39 micron = 21m ²
Hardness	: H8
Used on	: Concrete, steel, aluminium, plastics, wood, gypsum
Application field	: Stations, bridges, exteriors, interiors

SI21 is an incredibly strong 2-component paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.


Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating does not absorb any water or dirt
- Resistant to all kinds of chemicals and UV radiation
- Graffiti will be easy to remove
- This coating can withstand temperatures of 300°C

Expected life duration up to 30 years+




How to use: Page 24





APPLY
MOVIE SCAN
OR CODE



SI13

2-Component (2K)

Paint Coolest White for egg-shell surfaces

Product ID	: SI132000 2L / 3.300gr
Consumption	: 2 layers +/- 235gr/m ² - 143ml/m ² 90 micron = 14m ²
Reachable area	: 1 layer +/- 118gr/m ² - 72ml/m ² 45 micron = 28m ²
Hardness	: H7
Used for	: Concrete, steel, wood, acrylic, gypsum
Application field	: Buildings, airports, offshore structures, bridges

SI13 is an incredibly strong 2-component paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating is permanent hydrophobic.
- Resistant to all kinds of chemicals and UV radiation.
- This coating can withstand temperatures of 300°C

Expected life duration up to 25 years+



How to use: Page 24



SI15

1-Component (1K)

Paint Coolest White for egg-shell surfaces

Product ID	: SI152000 2L / 3.000gr
Consumption	: 2 layers +/- 235gr/m ² - 143ml/m ² 90 micron = 14m ²
Reachable area	: 1 layer +/- 118gr/m ² - 72ml/m ² 45 micron = 28m ²
Hardness	: H6
Used for	: Concrete, steel, wood, acrylic, gypsum
Application field	: Buildings, airports, offshore structures, bridges

SI15 is an incredibly strong 1-component paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating is permanent hydrophobic..
- Resistant to all kinds of chemicals and UV radiation.
- This coating can withstand temperatures of 300°C

Expected life duration up to 20 years+



How to use: Page 24





SI41

2-Component (2K)

Paint Textured White for semi gloss surfaces

Article Nr.	: SI412000 2L / 2.400 gr
Consumption	: 3 layers +/- 200gr/m ² - 165ml/m ² 105 micron = 12m ²
Reachable area	: 2 layers +/- 130gr/m ² - 110ml/m ² 70 micron = 16m ²
	: 1 layer +/- 65gr/m ² - 55ml/m ² 35 micron = 24m ²
Hardness	: H9
Used for	: Steel, aluminum, concrete, acrylic, wood
Application field	: Stations, tunnels, exteriors, interiors

SI41 Textured Armored High Impact Resistance Coatings and Paints are super strong and contain a sprayable nanoparticle, this nanoparticle ensures that less heat is transferred to the metal plates, resulting in a lower temperature of the plate and a lower temperature under the plate.

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating does not absorb any water or dirt
- Resistant to all kinds of chemicals and UV radiation.
- This coating can withstand temperatures of 300°C

Expected life duration up to 30 years+



How to use: Page 24



SI42

2-Component (1K)

Paint Textured White for semi matte surfaces

Article Nr.	: SI422000 67oz / 2.500gr
Consumption	: 3 layers +/- 200gr/m ² - 165ml/m ² 105 micron = 12m ²
Reachable area	: 2 layers +/- 130gr/m ² - 110ml/m ² 70 micron = 16m ²
	: 1 layer +/- 65gr/m ² - 55ml/m ² 35 micron = 24m ²
Hardness	: H9
Used for	: Steel, aluminum, concrete, acrylic, wood
Application field	: Stations, tunnels, exteriors, interiors

SI42 Textured Armored High Impact Resistance Coatings and Paints are super strong and contain a sprayable nanoparticle, this nanoparticle ensures that less heat is transferred to the metal plates, resulting in a lower temperature of the plate and a lower temperature under the plate.

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating does not absorb any water or dirt
- Resistant to all kinds of chemicals and UV radiation.
- This coating can withstand temperatures of 300°C

Expected life duration up to 30 years+



How to use: Page 24





SI31

2-Component (2K)

Topcoat Textured Transparent for semi gloss surfaces

Article Nr.	: SI312000 2L / 2.000gr
Consumption	: 3 layers +/- 225gr/m ² - 225ml/m ² 90 micron = 9m ²
Reachable area	: 2 layers +/- 150gr/m ² - 150ml/m ² 60 micron = 18m ²
	: 1 layer +/- 75gr/m ² - 75ml/m ² 30 micron = 27m ²
Hardness	: H7
Used for	: Concrete, natural stone, steel, wood
Application field	: Stations, tunnels, exteriors, interiors

SI31 is an armored super strong nano particle textured 2-component thermal insulation paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.

And results in this case in an anti-slip surface

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating does not absorb any water or dirt
- Resistant to all kinds of chemicals and UV radiation.
- This coating can withstand temperatures of 300°C

Expected life duration up to 20 years+ (Floors)



How to use: Page 28



SI33

2-Component (1K)

Paint Textured Roadmark Traffic Yellow and Black

Article Nr.	: SI332000-TY SI332000-BL 2L / 2.000gr
Consumption	: 3 layers +/- 225gr/m ² - 225ml/m ² 90 micron = 9m ²
Reachable area	: 2 layers +/- 150gr/m ² - 150ml/m ² 60 micron = 18m ²
	: 1 layer +/- 75gr/m ² - 75ml/m ² 30 micron = 27m ²
Hardness	: H7
Used for	: Concrete, natural stone, steel, wood
Application field	: Stations, tunnels, exteriors, interiors

SI33 is an armored super strong nano particle textured 2-component thermal insulation paint system which forms a durable matrix of molecular bonds (transformation to ceramic) resulting in permanent protection of the surface.

And results in this case in an anti-slip road marker

Three simple steps: Clean, Dry, and Apply.

- Easily repels water, dirt, dust, and pollutants.
- This coating does not absorb any water or dirt
- Resistant to all kinds of chemicals and UV radiation.
- This coating can withstand temperatures of 300°C

Expected life duration up to 20 years+ (Floors)



How to use: Page 28



SIX1

2-Component (2K)

Primer Epoxy Polyamide

heavy duty - anti-corrosion

Article Nr.	: SIX11250 1.25L / 1.2kg SIX15000 5L / 4.8kg
Consumption	: 2 layers +/- 240gr/m ² - 250ml/m ² 80 micron = 5m ²
Reachable area	: 1 layer +/- 120gr/m ² - 125ml/m ² 40 micron = 10m ²
Hardness	: H5
Colors	: White, Grey or RAL (RAL Minimum Order 250pcs 5L)
Used on	: Concrete, Steel, Aluminium, Fiberglass and other organic surfaces
Application area	: Buildings, marine, airports, offshore structures, bridges

SIX1 is a solvent based epoxy polyamide primer. This primer is used for corrosion protection on concrete, stainless, galvanized, carbon and alloy steel, aluminum in corrosive conditions and has excellent adhesion to all organic substrates and to all of our ceramic topcoats. The primer can be applied at a relative humidity of 40-80% and can be painted over within 8 hours 30°C, 1 hours 60°.



Fast Repaintable



Excellent adhesion



Heavy Duty Primer - Smooth Surfacer

SIX2

2-Component (2K)

Primer Surfacer Acrylic Alkyd

smooth - surface modifier

Article Nr.	: SIX21250 1.25L / 1.2kg SIX25000 5L / 4.8kg
Consumption	: 2 layers +/- 200gr/m ² - 210ml/m ² 60 micron = 6m ²
Reachable area	: 1 layer +/- 100gr/m ² - 105ml/m ² 30 micron = 12m ²
Hardness	: H3
Colors	: White, Grey
Used on	: Steel, aluminium, wood, fiberglass, and old paint systems.
Application area	: Buildings, hotels, private housing, etc.

SIX2 High-quality 2K surfacer (two-component basecoat) for auto-refinish, marine, and industrial coating applications where a smooth surface is required. The primer has excellent adhesion to all organic substrates and to all of our ceramic topcoats. The primer can be applied at a relative humidity of 30-80% and can be painted over within 4 hours 30°C, 1 hours 60°.



Fast Repaintable



Excellent adhesion



SIX3

2-Component (2K)

Primer PU Wood Filler

surface modifier - absorption reducer

Article Nr.	: SIX31500 1.5L / 1.4kg
Consumption	: 2 layers +/- 175gr/m ² - 185ml/m ² 60 micron = 8m ²
Reachable area	: 1 layer +/- 115gr/m ² - 95ml/m ² 30 micron = 12m ²
Hardness	: H4
Colors	: Transparent
Used on	: Wood, Natural Stone, and other organic surfaces
Application area	: Buildings, marine, hotels, private housing, etc.

SIX3 is a solvent borne transparent wood filler. This primer is used as surface modification for, wood or natural stone to reduce capillary absorption and has an excellent adhesion to all organic substrates and towards one of our ceramic top coats. The primer can be applied at a relative humidity of 40-80%.



Fast Repaintable



Excellent adhesion



Wood or Natural Stone - Filler

SIX4

1-Component (1K)

Primer Acrylic Waterbased

all surfaces modifier

Article Nr.	: SIX41000 1L / 1.2kg SIX44000 4L / 4.8kg
Consumption	: 2 layers +/- 240gr/m ² - 200ml/m ² 60 micron = 5m ²
Reachable area	: 1 layer +/- 120gr/m ² - 100ml/m ² 30 micron = 10m ²
Hardness	: H3
Colors	: White, Grey or RAL (RAL Minimum Order 250pcs 4L)
Used on	: Concrete, wood, drywalls and old waterbased paints
Application area	: Buildings, walls and ceilings indoor or outdoor

SIX4 Acrylic Water-Based Primer is a premium, all-purpose primer-sealer with excellent adhesion, stain-blocking, and hiding power. Ideal for both interior and exterior surfaces, it bonds to glossy surfaces without sanding, effectively blocks stains, and provides a smooth foundation for any solvent-based or water-based topcoat.



Fast Repaintable



Excellent adhesion



VOC Free



SIX5 2-Component (2K)

Putty Polyester ultra smooth - sandable

- Article Nr.:** : SIX51000 1.0kg
- Colors:** : Grey
- Used on:** : Metal, wood, fiberglass, concrete, plastics
- Application area:** : Buildings, marine, airports, offshore structures, bridges private housing, etc.



- Fast Repaintable**
- Excellent adhesion**

SIX5 is a High quality 2 (two) component Epoxy base putty for auto-refinish, marine and industrial coating applications.



Substrate Kit, Test, Touch and Feel

Substrate Kit
16 different coating and paints



DEMOSKIT
All our products are produced according to EU/ECHA USA/OSHA/EPA CANADA/WHIMS regulations

Video Application & (Test) Results

SGS TEST REPORTS SCAN QR-CODE

TECHNICAL VIDEO SCAN QR-CODE

TEST REPORT EN 1504-2 SCAN QR-CODE

Scan QR Code for TDS and SDS

NANO-CERAMIC®
WWW.NANO-CERAMIC.COM THE NEXT GENERATION COATINGS

2K CERAMIC COATING
Super Durable Utilizes Nano-Technology
UV / Chemical / 300°C / 600°F Resistant

WARNING!
FLAMMABLE - LIQUID VAPOR AND SPRAY MIST HARMFUL
EXPOSURE MAY CAUSE LUNG DAMAGE, ALLERGENIC REACTION OR RESPIRATORY REACTION. HARMFUL IF SWALLOWED. MAY CAUSE EYE, SKIN, NOSE AND THROAT IRRITATION.

GLOSS **TRANSPARENT / COLORABLE** **TRANSPARENT**

TDS **SDS**



How to use our Permanent Coating System:

These products can be stored for up to 24 months (in a dry, temperature-stable dark environment)

Processing Temperature:

Ambient temperature: 5-30°C
Avoid direct sunlight, Rain and /or high humidity.

IMPORTANT:

Before you use a NANO-CERAMIC product, please make sure you wear suitable protection gear. We always recommend using a paint suit, respirator mask and latex or nitrile gloves.

Outfit/Applicators:



Fresh Air Respirator



Paint Suit



Nitrile gloves



Professional Paint Sprayer
1.3-1.7mm / 0.05-0.06" nozzle



Paint Roller
(Microfiber)



Respirator



Paint Brush
(acrylic)

Application information

The SI11/SI12/SI21/SI22/SI13/SI15/SI31/SI33/SI41/SI42 coatings can be applied directly or indirectly on all surfaces (porous and non-porous) such as concrete, steel, wood, acrylic, gypsum, painted or unpainted surfaces, indoors, or outdoors. The surface underneath will be superbly protected against erosion and corrosion and will stay cleaner longer. Cleaning becomes quicker, easier, and less expensive, as special cleaning agents are unnecessary.

Preparation

Make sure the surface is free from any contamination and dirt. A zinc rich primer can be used in case of problems with the substrate.

Warning the surface must be completely dry before application and must stay dry for 6 hours after application after application!

The 2-Component Permanent Coating System

Mix the can SI11B-SI12B-SI21B-SI22B-SI13B-SI31B-SI41B-SI42B with the can of SI11A-SI12A-SI21A-SI22A-SI13A-SI31A-SI41A-SI42A by pouring can B into can A, or measure exactly by net weight in a ratio of 9:1 and mix very well.

Carefully pour the mixed contents into a professional paint sprayer, and spray in thin layers until the surface reaches your desired thickness. Depending on the surface, material and structure, different application techniques can be used (such as paint rollers or brushes). Let the surface dry for 24 hours. It is touch-dry in 1 hours, after 4 hours, 85% cured, and the remaining 15% (transformation into ceramics) is fully cured after 7 days.

Be aware that the mixed contents cannot be stored longer than 3 hours. The surface can simply be maintained with a high pressure washer at 80 bar using our biologically degradable Reactivating Shampoo SHRE.

Tool cleaning

The individual components, as well as the mixing system of the paint sprayer, can be diluted and cleaned using our THIN Thinner Solvent.

SOLV

 Thinner solvent

for all types of our ceramic paint & coating



Article Nr. : SOLV0400 400ml / 345gr

All our paints and coatings are ready to use, for certain spray applications, especially dark colors who require more than average color pigments, it may be necessary to use a little thinner solvent to achieve optimum flowability.

RETA/ACCL

 Retarder
Accelerator


slow down flash time or speed up curing

Article Nr. : RETA0400 400ml / 345gr ACCL0200 200ml / 180gr


If your application need longer flash time (longer time to build up the layer with a second or third coat you can add the RETA Retarder.

In case you want to speed up the curing process you can add the ACCL Accelerator.


Where to use our coatings:




Color Retention QUV Accelerated Testing (ASTM D4587)



Corrosion Tests



Gloss Retention QUV Accelerated Testing (ASTM D4587)



Video Application & (Test) Results



Color card

Other colors need minimal 100kg

Residential

SI13 White Egg-Shell (Flat Finish) 15/25 (20/60°)	SI41 Textured White Semi Gloss 41/69 (20/60°)
SI15 White Egg Shell (Flat Finish) 18/28 (20/60°)	SI42 Textured White Matte 11/21 (20/60°)
SI21 White Gloss 49/77 (20/60°)	
SI22 White Satin 33/59 (20/60°)	

Original, Cool white, Cream white, Grey white, Signal white, Signal black, Jet black, White aluminium, Grey aluminium, Pure white, Graphite black, Traffic white

RAL 9018 Papyrus white, RAL 9001, RAL 9002, RAL 9003, RAL 9004, RAL 9005, RAL 9006, RAL 9007, RAL 9010, RAL 9011, RAL 9016

RAL 3015 Light pink, RAL 6007 Pastel blue, RAL 4009 Pastell violet, RAL 6027 Light green, RAL 7000 Squirrel grey, RAL 1036 Pearl gold, RAL 8029 Pearl copper, RAL 4012 Pearl blackberry, RAL 6025 Pearl gentian blue, RAL 6036 Pearl opal green, RAL 8016 Mahogany braun

Wood

SI11 Transparent Gloss 51/78 (20/60°)
SI12 Transparent Matte 11/21 (20/60°)

SI11 Transparent, SI11 Light, SI11 Nut, SI11 Colonial

Industrial

SI11 Transparent Gloss 51/78 (20/60°)
SI21 White Gloss 49/77 (20/60°)
SI22 White Satin 33/59 (20/60°)

Transparent, Lumious yellow, Traffic red, Jet black, Golden yellow [Cat], Leaf green [J.D Deere], Light grey, Dark grey, Silver grey, Signal brown, Pale brown

RAL 1026, RAL 3020, RAL 9005, RAL 1004, RAL 6002, RAL 7035, RAL 7011, RAL 7003, RAL 8002, RAL 8025

Marine

SI12 Transparent Matte 11/21 (20/60°)
SI41 Textured White Semi Gloss 41/69 (20/60°)
SI42 Textured White Matte 11/21 (20/60°)

Cool white, Pure white, Cream white, Distant blue, Traffic yellow, Silver gray, Light Ivory, Pure white, Cream, Beige, Olive yellow

RAL 9010, RAL 9001, RAL 9023, RAL 1023, RAL 7001, RAL 1015, RAL 9016, RAL 9001, RAL 1001, RAL 1020

Military

SI31 Textured Transparent Semi Gloss 41/69 (20/60°)
SI33 Textured Black Semi Gloss 41/69 (20/60°)

Transparent matte, Blue grey, Jet black, NATO green, Graphite grey, Desert sand, Camo beige, Dark grey camo, Dark brown camo, Olive drap, Very dark drap

RAL 7031, RAL 9005, RAL 6005, RAL 7024, RAL 1015, RAL 9000, RAL 9012, RAL 9002, RAL 9013, RAL 5005

Antifouling

SI14 Color 3141 (20/60°)

Transparent, Jet Black, Signal Red, Ultra marine blue, Signal Grey

RAL 9005, RAL 3001, RAL 5002, RAL 7004



NANO-CERAMIC®



WWW.NANO-CERAMIC.COM INDUSTRIAL PROTECTIVE COATINGS

There is no better option than to use
NANO-NANO-CERAMIC®



The Leader in Durability

Did you know?

*Our coatings are made of
pure silica sand, which is
the most common element
on Earth?*

Dealer